

# Safety Data Sheet (SDS)



## Diesel Max

SDS Number: 60065

Revision Date: 6/16/2015

Page 1 of 1

### Section 1: Product and Company Identification

#### Manufacturer

Bade Incorporated  
48 Sulfur Springs Road  
Irwin, PA 15642

Phone: 1-800-783-0363

**Product Name:** Diesel Max  
**Revision Date:** 6/16/2015  
**SDS Number:** 60065  
**CAS Number:** Blend  
**Product Code:** 60065  
**Synonyms:** Diesel Fuel Additive

For emergencies contact Chemtrec at 1-800-424-9300.

### Section 2: Hazards Identification

GHS Signal Word:  
DANGER

GHS Hazard Pictograms:



GHS Classifications:

Physical, Flammable Liquids, 3  
Health, Specific target organ toxicity – Single exposure, 3  
Health, Skin corrosion/irritation, 2  
Health, Serious Eye Damage/Eye Irritation, 2 A  
Health, Aspiration hazard, 1  
Health, Carcinogenicity, 2  
Environmental, Hazards to the aquatic environment - Chronic, 3

GHS Phrases:

H226 – Flammable liquid and vapor  
H335 – May cause respiratory irritation  
H336 – May cause drowsiness or dizziness  
H315 – Causes skin irritation  
H319 – Causes serious eye irritation  
H304 – May be fatal if swallowed and enters airways

# Safety Data Sheet (SDS)



## Diesel Max

SDS Number: 60065

Revision Date: 6/16/2015

Page 2 of 4

### GHS Precautionary Statements:

P302+352 - IF ON SKIN: Wash with soap and water.

P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present if easy to do. Continue rinsing.

P273 - Avoid release to the environment.

### Section 3: Composition/Information on Ingredients

#### Ingredients:

Chemical Name	Percentage	CASE No.
Light aromatic solvent naphtha	40.0 – 50.0	64742-95-6
Ethylene glycol monobutylether	10.0 – 20.0	111-76-2
1,2,4-Trimethylbenzene	< 25.0	95-63-6
Xylene	< 3.0	1330-20-7
Cumene	<1.0	98-82-8
Ethylbenzene	<1.0	100-41-4
Trimethylbenzene	<1.0	25551-13-7
Heavy aromatic solvent naphtha	<1.0	64742-94-5
1,3,5-Trimethylbenzene	<1.0	108-67-8
Vinyl acetate monomer	<0.1	108-05-4
Naphthalene	<0.1	91-20-3

### Section 4: First Aid Measures

**Inhalation:** If symptoms develop, move victim to fresh air.  
If symptoms persist, obtain medical attention.

**Skin Contact:** Wash with soap and water.  
Remove contaminated clothing and wash before reuse.  
Get medical attention if needed.

**Eye Contact:** Flush with water for several minutes.  
If effects occur, consult a physician.

**Ingestion:** Rinse mouth with water and drink 2-4 cups of water.  
Get immediate medical attention.

**Note to Physician:** Activated charcoal may be administered.

### Section 5: Fire Fighting Measures

**Flash Point:** 49.0 C (120.2F)

**Flash Point Method:** PMCC

Use dry powder, foam, or carbon dioxide fire extinguishers.

Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

## Diesel Max

SDS Number: 60065

Revision Date: 6/16/2015

Page 3 of 4

### Section 6: Accidental Release Measures

Eliminate sources of ignition – Heat, sparks, flame and electricity  
Contain spilled material.  
Collect insuitable and properly labeled containers.  
Pickup excess with inert absorbent material.  
Keep away from drains and ground water.

### Section 7: Handling and Storage

**Handling Precautions:** Avoid contact with eyes, skin, or clothing.  
Keep away from sources of ignition.  
Do not pressurize, cut, weld, braze, solder, drill or grind containers.  
Handle with care and avoid spillage on the floor (slippage).  
Ground and bond containers when transferring material.

**Storage Requirements:** Keep away from sources of ignition.  
Store in a tightly closed container.

### Section 8: Exposure Controls/Personal Protection

**Engineering Controls:** All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

**Personal Protective Equip:** Use of safety glasses and gloves are recommended.

**EXPOSURE GUIDELINES:** LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)  
OSHA TWA: 500 ppm  
1,2,4-TRIMETHYLBENZENE  
ACGIH TWA: 25 ppm  
XYLENE  
OSHA TWA: 100 ppm, 435 mg/m<sup>11</sup> 3  
ACGIH TWA: 100 ppm, 434 mg/m<sup>11</sup> 3  
OSHA STEL: 150 ppm, 655 mg/m<sup>11</sup> 3  
ACGIH STEL: 100 ppm, 651 mg/m<sup>11</sup> 3  
CUMENE  
OSHA PEL: 50 ppm  
OSHA TWA: 50 ppm, 245 mg/m<sup>11</sup> 3  
ACGIH TWA: 50 ppm, 246 mg/m<sup>11</sup> 3

### Section 9: Physical and Chemical Properties

Appearance: Amber  
Physical State: Liquid  
Spec Grav/Density: 0.883 at 60 F (Water=1)  
Viscosity: 4.0 est at 40 degrees C  
Solubility: Nil in water

### Section 10: Stability and Reactivity

**Stability** Product is stable under normal conditions.  
**Conditions to Avoid:** High temperatures and open flame.  
**Materials to Avoid:** Avoid strong oxidizing agents  
May burn or react violently to  
fluorine/oxygen mixtures



# Safety Data Sheet (SDS)

## Diesel Max

SDS Number: 60065

Revision Date: 6/16/2015

Page 4 of 4

### Section 11: Toxicological Information

Repeated skin contact with this product may cause dermatitis or an oil acne. No component is listed as a carcinogen, mutagen, or teratogen.

#### SKIN EFFECTS:

Solvent Petroleum Naphtha, no deaths reported at 4 ml/kg (rat). Slightly irritating (rabbit, 4 hours).  
Vinyl Acetate Monomer, Skin absorption LD50 is 2,335 mg/kg in rabbits.

#### ACUTE ORAL EFFECTS:

Solvent Petroleum Naphtha, LD 50, 10 ml/kg in rats.  
Oral LD50 for Vinyl Acetate Monomer is 2,920 mg/kg in rats.

#### ACUTE INHALATION EFFECTS:

Solvent Petroleum Naphtha, no deaths at 710 ppm (v) (Rate) 4 hours.  
Vinyl Acetate Monomer, four hour inhalation LC50 is 4,000 ppm in rats.

### Section 12: Ecological Information

Avoid exposing to the environment, no specific aquatic data available

### Section 13: Disposal Considerations

Dispose of in accordance with local, state/  
provincial and national requirements.

Do not flush to surface water or drain

### Section 14: Transport Information

UN#: NA 1993, Class: -, Proper Shipping Name; Combustible liquid, n.o.s.

This material is not regulated for US DOT transportation in quantities less than 119 gallons.

If shipping overseas or via air, the proper shipping name is: Flammable liquid, n.o.s. (Contains Petroleum Naphtha, Ethylene Glycol Monobutyl Ether), 3 UN 1993, PGIII.

### Section 15: Regulatory Information

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act (TSCA).

### Section 16: Other Information

The information contained in this Safety Data Sheet relates only to the specific material designated. Bade, Incorporated assumes no legal responsibility for use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Bade, Incorporated.